








Preliminary Results of ANAIS-25 at the Canfranc Underground Laboratory

María Luisa Sarsa





Outline

Nal(TI) crystal Searching for radiopure NaIT(I) powder

ANAIS-0 ANAIS-25 AS 1k

The ANAIS
Experiment


PMT choice

Other results


Slow scintillation in NaI(TI) crystals




The ANAIS Experiment



250 kg of ultrapure NaI(TI)
detectors at the Canfranc
Underground Laboratory (LSC)





Goal: study the annual modulation in the dark matter signal





The ANAIS Experiment

Long effort in R+D at the University of Zaragoza through the operation of several prototypes

- HPGe radiopurity test bench for material selection: specially Nal powder from different providers
- PMT Testing
- Light collection efficiency study
- Background understanding / simulations
- Optimization of data analysis and readout
















ANAIS-O Prototype

ANAIS-0 consists of a 9,6 kg NaI(TI) crystal made by Saint Gobain 4"x4"x10"












2009-2012






ANAIS-O shielding

- 10 cm archaeological lead
- 20 cm low activity lead
- Tightly closed box kept with boil-off nitrogen overpressure
- Three plastic scintillators as muon vetoes

odule



ANAIS-O DATA READOUT




- Bus VME/NIM
- Two signal lines/module symmetrical
- Trigger: logical AND (200ns coincidence window)
- Energy estimator: QDC in three different dynamic ranges
- Pulse shape: MATACQ card (2GS/s, 12 bit vertical resolution, 1,25 μs window)
- SCALABLE FOR ANAIS
- TESTED WITH TWO MODULES
- FULLY COMMISSIONED



MUON RELATED EVENTS have been identified and removed from data


- 1. Events coincident with a muon in the plastic scintillators
- 2. Events 0.5 s after a very high energy deposition (muons but not only...)



We want to select real bulk Nal scintillation events


CUTS have been developed for:


- Rejection of PMT origin events



We count the total number of peaks (ph.e.) in every low energy event

n>3 for each PMT








We want to select real bulk Nal scintillation events

CUTS have been developed for:


- Rejection of PMT origin events




We count the total number of peaks (ph.e.) in every low energy event

n>3 for each PMT

- Rejection of anomalous fast events



After filtering, 3.2 keV peak appears in our background







ANAIS-0: Background Model

We have built a background model for the ANAIS-0 module, based on radiopurity input data for the different detector and shielding components.

Simulations have been done using Geant-4










ANAIS-0: Background Model

We have built a background model for the ANAIS-O module, based on radiopurity input data for the different detector and shielding components.

Simulations have been done using Geant-4
With slight and motivated modifications to this model we achieve a
remarkable agreement



S. Cebrián et al., Astroparticle Physics 37 (2012) 60



Searching for radiopure Nal powder

HPGe spectrometry screening at LSC of K content in NaI powder from different providers.

Goal: Potassium content @ 0.02 ppm (or below)

	AS Nal powder	LIMITS AT 95% C.L.
Nal powder	Potassium	<0.09 ppm
Merck - commercia	Uranium-238	<0.055 ppb
Alfa-Aesar — commercial	Thorium-232	<0.13 ppb
ESI - purified	0.32 ± 0.00	8
AS – selected	<0.09 (95% (Alpha Spectra, Inscrint Scintillation Detector




Crystal Growing and Manufacturing

Two 12.5 kg cylindrical crystals were grown and encapsulated by AS with the best raw powder:

- cylindrical in shape 4.75" diameter x 11.75" length
- encapsulated in OFHC copper, with an aluminized Mylar window to allow low energy calibrations.


Protocols for low-background machining, selection of materials to be used, surface cleaning procedures, etc. were proposed by the UZ, discussed and agreed by AS











ANAIS-25 set-up

12.5 kg detectors made by AS arrived to Spain at the end of November 2012


They were coupled to ULB and VLB PMTs at LSC clean room

No light guides were used

Measurements started very fast



ANAIS-25 set-up



Taking data at LSC since December 2012


Same shielding and readout from ANAIS-0

Main goals: determine potassium content and general performance asessment





ANAIS-25: Potassium Content

Measured by coincidence



Result for ⁴⁰K bulk activity of the ANAIS-25 crystals: 1.25 ± 0.11 mBq/kg (i.e. 41.7 ± 3.7 ppb K)






Very low energy TAGGED population -> useful


ANAIS-25: Light collection efficiency

Remarkable light collection efficiency

PMT model	ANAIS-0	ANAIS-25
	phe/keV	phe./keV
Ham. R12669SEL2	7.38±0.07	16.13±0.66
Ham. R11065SEL	5.34±0.05	12.58±0.13




- Very good optical quality of the crystals
- Mo light guides used
- High quantum efficiency PMTs




ANAIS-25: Trigger @ ph.e.

Trigger at ph.e. level is achieved Trigger efficiency has been studied with the 3.2 keV peak selected by coincidence




ANAIS-0



ANAIS-25

More than 97% of the events above 1.5 keV are triggering

ANAIS-25: Cosmogenic Activation




Main isotopes activated cosmogenically identified in ANAIS-25 data

Isotope	Lifetime	Decay	Main emissions
	days		keV
¹²⁵ I	59.4	EC	35.5
^{126}I	13.11	EC, β^-	666.0
121m Te	154	IT, EC	294.0
¹²¹ Te	16.8	EC	507.6, 573.1
^{123m} Te	119.7	IT	247.6
^{125m} Te	57.4	IT	144.8
^{127m} Te	109	IT, β^-	88.3

Contribution from Radon inside the shielding + isotopes activated cosmogenically along 75 first day of data




ANAIS-25: Alpha Events



Alpha particles are clearly distinguished from PSA


Very high alpha rate: 3,15 mBq/kg

Spectrum indicates natural chains out of equilibrium with a dominant contribution





ANAIS-25: Alpha Events



Alpha particles are clearly distinguished from PSA

Very high alpha rate: 3,15 mBq/kg


We have searched for coincident events from ²¹²Bi-Po and ⁴¹ ²¹⁴Bi-Po coincidences in a dedicated set-up

Above the main alpha peak



ANAIS-25: Background Model

Our background model (without cosmogenic isotopes) reproduces nicely most of the low energy background





AS 1k measurement

High alpha rate in ANAIS-25 modules




1 kg crystal from a new grown NaI(TI) ingot @

AS — NUDE & mounted at the UZ

For measuring alpha rate


(August 2013)





2013







Ham LB

Ham ULB

Ham VLB

PMT Testing

HP Ge spectrometry at LSC





Model	⁴⁰ K	^{232T} h	2328 _U
	(mBq/PMT)	(mBq/PMT)	(mBq/PMT)
HAM - R6233-100	678 ± 42	68 ± 3	100 ± 3
HAM-LB			
HAM - R11065SEL	12 ± 7	3.6 ± 1.2	²³⁸ U: 47 ± 28
HAM-ULB			²²⁶ Ra: 8.0 ± 1.2
HAM - R6956MOD	97± 18	20 ± 2	²³⁸ U: 128 ± 38
HAM-VLB			²²⁶ Ra: 84 ± 3






Ham ULB

Ham VLB

PMT Testing

Direct Measurement in ANAIS-0 prototype

We would like to avoid LG: is PMT background so relevant?




Slow Scintillation Constants in NaI(TI) To appear in Optical Materials

http://arxiv.org/abs/1307.1398

- Ph.e. have been identified individually after every high energy event and their time arrival saved in a 300 ms window
- Mistograms are built separately for alpha and gamma events
- Four large crystals from different manufacturers have been

studied



ANAIS-25



Slow Scintillation Constants in NaI(TI) To appear in Optical Materials

http://arxiv.org/abs/1307.1398

- Mean times in the range 75-90 ms are obtained for all the crystals studied
- Gamma/Muon events produce much more effectively this slow scintillation
- It is able to trigger in AND mode two PMTs in a dark matter search!!

Detector	$N_{\alpha}/N_{\gamma/\mu}$	$\tau_{\alpha,mean} \text{ (ms)}$	$\tau_{\gamma/\mu,mean} \; (\mathrm{ms})$
ANAIS-0	0.4 ± 0.2	75.5	80.3
PIII	0.8 ± 0.2	68.3	69.0
D0	0.5 ± 0.1	92.1	101.7
D1	0.4 ± 0.1	88.3	99.5



Outlook

- Mal powder at 40ppb potassium level has been found -> further improvement should be possible, (see SABRE talk)
- NaI(TI) detectors with outstanding light collection efficiency have been built by AS UZ
- ²¹⁰Pb (probably from ²²²Rn) is a problem: AS is improving their protocols and we look forward cleaner crystals -> AS 1k result is promising
- Electronics, acquisition software and analysis is reliable and has been thorougly tested
- Good understanding of background at high and low energy

Prospects

- MANAIS-25 filtering procedure still developing
- MANAIS 250kg simulation will be ready soon ⁴⁰K is rejected by coincidences between modules and large size of our crystals is also an advantage to prevent 1461 keV gamma from escaping
- Working with AS to get as soon as possible a new improved prototype Progress and data are being shared with DM-ice collaboration
- Hopefully we could grow ANAIS crystals along 2014